

UNIVERSIDAD DE CANTABRIA

**DEPARTAMENTO DE CIENCIA E INGENIERÍA DEL TERRENO
Y DE LOS MATERIALES**

TESIS DOCTORAL

**EVALUACIÓN DE LA INTEGRIDAD ESTRUCTURAL DE
COMPONENTES SOMETIDOS A CONDICIONES DE
BAJO CONFINAMIENTO**

Autor:

SERGIO CICERO GONZÁLEZ

Director:

D. FEDERICO GUTIÉRREZ-SOLANA SALCEDO

Tesis Doctoral presentada en la Universidad de Cantabria para la obtención del
Título de Doctor Ingeniero de Caminos, Canales y Puertos

Santander, Marzo de 2007

CAPÍTULO 8

BIBLIOGRAFÍA

- [1] Griffith, A.A., “*The Phenomena of Ruptura and Flow in Solids*”, Phil. Trans. R. Soc. London. A 221, 163-198 (1920).
- [2] Irwin, G.R., “*Analysis of Stresses and Strains Near the End of a Crack Traversing a Plate*”, Trans. J. Appl. Mech. 24, 361-364 (1958).
- [3] Williams, M.L., “*On the Stress Distribution at the Base of Stationary Crack*”. Journal of Applied Mechanics, Vol. 24, p. 109-114 (1957).
- [4] Elsheby, J.D., Solid State Phys., Vol.3, p.79-144 (1956).
- [5] Paris, P.C., Gomez, R.E., Anderson, W.E., “*A Rational Analytic Theory of Fatigue*”, The Trend in Engineering, Vol.13, nº1 (1961).
- [6] Paris, P.C., “*The Fracture Mechanics Approach to Fatigue*”, Proceedings of the Tenth Sagamore Army Materials Research Conference, Syracuse University Press (1964).
- [7] Burdekin F.M. y Stone D.E.W., “*The Crack Opening Displacement Approach to Fracture Mechanics in Yielding Materials*”. Journal of Strain Analysis, Vol. 1, p.144-153 (1966)

- [8] Dugdale, D.S., “*Yielding in Steel Sheets Containing Slits*”. Journal of the Mechanics and Physics of Solids, Vol. 8, p.100-104.
- [9] McClintock, F.A., “*Plasticity Aspects of Fracture*”. Fracture: An Advanced Treatise, Vol. 3, Academia Press, New York, p. 47-225 (1971).
- [10] ASME Boiler and Pressure Vessel Code, “*Section XI, Rules for In-Service Inspection of Nuclear Power Plant Components*”, The American Society of Mechanical Engineers (1995).
- [11] British Standard BS 7910: “*Guide on Methods for Assessing the Acceptability of Flaws in Metallic Structures*”, BSi, London (2000)
- [12] R6: “*Assessment of the Integrity of Structures Containing Defects*”, British Energy Generation, Report R/H/R6, Revision 4 (2001).
- [13] SINTAP, “*Structural Integrity Assessment Procedure for European Industry*”, SINTAP BRITE-EURAM Project BRPR-CT95-0024 (1999).
- [14] FITNET, “*European Fitness-for-Service Network*”, EU’s Framework 5, Proposal No. GTC1-2001-43049, Contract No. G1RT-CT-2001-05071.
- [15] Pluvinage, G., Azari, Z., Kadi, N., Dlouhy, I., Kozak, V., “*Effect of Ferritic Microstructure on Local Damage Zone Distance Associated with Fracture Near Notch*”, Theoretical and Applied Fracture Mechanics 31, p. 149-156 (1999).
- [16] Kim, J.H., Kim, D.H., Moon, S.I., “*Evaluation of Static and Dynamic Fracture Toughness Using Apparent Fracture Toughness of Notched Specimens*”, Materials Science and Engineering A, Vol. 387-389, p.381-384 (2004).
- [17] Taylor, D., Cornetti, P. y Pugno, N., “*The Fracture Mechanics of Finite Crack Extension*”, Engineering Fracture Mechanics, 72, Issue 7, p. 1021-1038 (2005).
- [18] Gutiérrez-Solana, F., González, J., Setién, J., Varona, J.M., “*Guía de Estudio de Ciencia de los Materiales (II): Comportamiento Mecánico de los Materiales*”, Servicio de Publicaciones de la ETS de Ingenieros de Caminos, Canales y Puertos de la Universidad de Cantabria (1995).

- [19] Tada, H., Paris, P.C., Irwin, G.R., “*The Stress Analysis of Cracks Handbook*”, 2nd Edition, Paris Productions, Inc., St. Louis (1985).
- [20] Murakami, Y., “*Stress Intensity Factors Handbook*”, Pergamon Press, New York (1987).
- [21] Rooke, D.P., Cartwright, D.J., “*Compendium of Stress Intensity Factors*”, Her Majesty’s Stationery Office, London (1976).
- [22] ASTM, “*Standard Test Method for Plane Strain Fracture Toughness of Metallic Materials*”, E399-83, Philadelphia (1983).
- [23] Brown, W.F. Jr., Srawley, J.E., “*Plane Strain Crack Toughness Testing of High Strength Metallic Materials*”, ASTM STP 410, American Society for Testing and Materials, Philadelphia (1966).
- [24] Anderson T. L., “*Fracture Mechanics: Fundamentals and Applications*”, 2nd edition, CRC Press, Boca Raton, (1995).
- [25] Broek, D., “*Elementary Engineering Fracture Mechanics*”, 3rd Edition, Martinus Nijhoff, The Hague (1982).
- [26] Rice, J.R., “*A Path Independent Integral and the Approximate Analysis of Strain Concentration by Notches and Cracks*”, Journal of Applied Mechanics, Vol.35, p. 379-386 (1968).
- [27] Ewalds, H.L., Wanhill, R.J.H., “*Fracture Mechanics*”, Edward Arnold Pub., Londres (1985).
- [28] Barenblatt, G.I., “*The Mathematical Theory of Equilibrium Cracks in Brittle Fracture*”, Advances in Applied Mechanics, Vol. III, Academic Press, p. 55-129 (1962).
- [29] Ruiz Ocejo, J., González-Posada, M.A., Gutiérrez-Solana, F., y Gorrochategui, I., “*Development and Validation of Procedures: Review of Existing Procedures*”, SINTAP Task 5, Report SINTAP/UC/04 (1997).

- [30] Ruiz Ocejo, J., González-Posada, M.A., Gorrochategui, I., Gutiérrez-Solana, F., “*Análisis Comparativo de los Procedimientos de Evaluación de la Integridad Estructural de Componentes Fisurados*”, Anales de Mecánica de la Fractura, 15, p. 115-119 (1998).
- [31] Ruiz Ocejo, J., González-Posada, M.A., Gorrochategui, I., Gutiérrez-Solana, F., “*Comparison Between Structural Integrity Assessment Procedures for Cracked Components*”, Fourth International Conference on Engineering Structural Integrity Assessment: Lifetime Management and Evaluation of Plant, Structures and Components, Cambridge, Reino Unido (Sept. 1998).
- [32] González-Posada, M.A., “*Influencia de la sustentación hiperestática en el criterio Fuga antes que Rotura aplicado a sistemas de tuberías en régimen elastoplástico*”, Tesis Doctoral, Escuela Técnica Superior de Ingenieros Industriales, Universidad de Cantabria (2004).
- [33] Paris, P.C. y Johnson, R.E., “*A Method of Applications of Elastic-Plastic Fracture Mechanics to Nuclear Vessel Analysis*”, Elastic-Plastic Fracture: Second Symposium, Vol. II- Fracture Resistance Curves and Engineering Applications, ASTM STP 803, C.F. Shih y J.P. Gudas, Eds., American Society for Testing and Materials, p. II-5-II-40 (1983).
- [34] Wilkoswski, G., Ahmad, J., Barnes, D., Brust, F., Ghadiali, N., Guerreri, D., Kiefner, J., Kramer, G., Landow, M., Marschall, C., Maxey, W., Nakgaki, M., Papaspyropoulos, V. y Scott, P., “*Degraded Piping Program-Phase II Progress*”, Nuclear Engineering and Design, Vol. 98, p. 195-217 (1987).
- [35] Golembiewski, H.J. y Vasoukis, G., “*On the Required Toughness for the Application of the Net Section Criterion on the Nuclear Power Plant Components*”, Nuclear Engineering and Design, Vol.87, p. 67-71 (1985).
- [36] Golembiewski, H.J. y Vasoukis, G., “*Influence of Material Properties and Geometry on the Limit Load Behaviour of Flawed Structures*”, International Journal Pressure Vessel and Piping, Vol.31, p. 131-140 (1988).

- [37] Ruiz Ocejo, J., González-Posada, M.A., Gorrochategui, I., Gutiérrez-Solana, F., “*Presente y Futuro de los Procedimientos de Evaluación de la Integridad Estructural de Componentes Fisurados*”, Anales de Mecánica de la Fractura, 14, p. 417-420 (1997).
- [38] Harrison, R.P., Loosemore, K. y Milne, I., R6: “*Assessment of the Integrity of Structures Containing Defects*”, CEGB Report R/H/R6 (1976).
- [39] Kumar, V., German, M.D. and Shih, C.F., “*An Engineering Approach for Elastic-Plastic Fracture Analysis*”, General Electric Company, NP-1931, Research Project 1237-1 Topical Report (1981).
- [40] R6: “*Assessment of the Integrity of Structures Containing Defects*”, British Energy Generation, Report R/H/R6, Revision 3 (1986)
- [41] Bergman, M., Brickstad, B., Dahlberg, L., “*A Procedure for Safety Assessment of Components with Cracks-Handbook*”, SAQ/FoU Report, 91/01, AB Svensk Anläggningsprovning, Swedish Plant Inspection Ltd, (1991)
- [42] “*Fitness for Service Guide*”, EXXON Chemical (1995)
- [43] “*Fitness for Service Evaluation Procedures for Operating Pressure Vessels, Tanks and Piping in Refinery and Chemical Service*”. Draft nº5, Consultants Report, The Materials Properties Council (Oct. 1995).
- [44] API 579, “*Recommended Practice for Fitness for Service*”, Draft Issue 4, American Petroleum Institute (1996).
- [45] PD6493, “*Guidance Methods for Assessing the Acceptability of Flaws in Fusion Welded Structures*”, BSi (1975)
- [46] Gorrochategui, I., Gutiérrez-Solana, F., Varona, J.M., “*Estudio Comparativo de Métodos Elastoplásticos de Cálculo de Estructuras Agrietadas*”, Anales de Mecánica de la Fractura, 9 (1992).
- [47] Schwalbe, K.H., Zerbst, V., Kim, Y.J., Brocks, W., Cornec, A., Heerens, J., Amstutz, H., “*The ETM Method for Assessing the Significance of Crack-Like Defects in*

- Engineering Structures, Comprising the Versions ETM 97/1 and ETM 97/2*”, GKSS-Forschungszentrum Geesthacht GmbH (1998).
- [48] Ainsworth, R.A., “*The Assessment of Defects in Structures of Strain Hardening Material*”, Engineering Fracture Mechanics, Vol. 19, Nº4, p. 633-642 (1984).
- [49] Kim, Y.J. y Huh, N.S., “*Enhanced Reference Stress-based J and Crack Opening Displacement Estimation Method for Leak-Before-Break Analysis and Comparison with GE/EPRI Method*”, School of Mechanical Engineering, Sungkyunkwan University, 300 Chunchun-dong, Jangangu, Suwon, Kyonggi-do, Korea (2000).
- [50] Turner, C.E, “*A J-Based Fracture Safe Estimation Procedure, En J, with Applications Including Estimation of the Maximum Load for Ductile Tearing*”, L.H.Larsson (ed.), Elastic-Plastic Fracture Mechanics, p. 411-426 (1985).
- [51] Bloom, J.M., “*Deformation Plasticity Failure Assessment Diagram*”, Elastic-Plastic Fracture Mechanics Technology, ASTM STP 896, J.C.Newman, Jr and F.J.Loss, Eds., American Society for Testing and Materials, Philadelphia, p. 114-127 (1985).
- [52] Ruiz Ocejo, J., Gutiérrez-Solana, F., González-Posada, M.A. , y Gorrochategui, I., “*Failure Assessment Diagram-Crack Driving Force Diagram COMPATIBILITY*”, SINTAP Task 5, Report SINTAP/UC/05 (1997).
- [53] VOCALIST, “*Validation of Constraint Based Assessment Methodology in Structural Integrity*”, FIKS CT-2000-00090, Fifth Framework of the European Atomic Energy Community (EURATOM).
- [54] Bilby, B.A., Cardew, G.E., Goldthorpe, M.R., y Howard, I.C., “*A Finite Element Investigation of the Effects of Speciment Geometry on the Fields of Stress and Strain at the Tip of Stationary Cracks*”, Size Effects in Fracture, Institute of Mechanical Engineers, p.37-46, London (1986).
- [55] Betegon, C. y Hancock, J.W., “*Two Parameter Characterization of Elastic-Plastic Crack Tip Fields*”, Journal of Applied Mechanics, Vol. 58, p. 104-110 (1991).
- [56] Kirk, M.T., Dodds, R.H., Jr., y Anderson, T.L., “*Approximate Techniques for Predicting Size Effects on Cleavage Fracture Toughness*”. Fracture Mechanics: 24th Volume, ASTM STP 1207, American Society for Testing and Materials, Phidadelphi.

- [57] O'Dowd, N.P. y Shih, C.F., “*Family of Crack-Tip Field Characterized by a Triaxiality Parameter-I. Structure of Fields*”. Journal of the Mechanics and Physics of Solids, Vol. 39, p. 898-1015 (1991).
- [58] O'Dowd, N.P. y Shih, C.F., “*Family of Crack-Tip Field Characterized by a Triaxiality Parameter-II. Fracture Applications*”. Journal of the Mechanics and Physics of Solids, Vol. 40, p. 939-963 (1992).
- [59] Shih, C.F., O'Dowd, N.P. y Kirk, M.T., “*A Framework for Quantifying Crack Tip Constraint*”. Constraint Effects in Fracture, ASTM STP 1171, American Society for Testing and Materials, p. 2-20, Philadelphia (1993).
- [60] Beremin, F.M., “*A Local Criterion for Cleavage Fracture of a Nuclear Pressure Vessel*”, Metall. Trans., Vol. 14^a, p. 2277-2287 (1983).
- [61] Beremin, F.M., “*Experimental and numerical study of the different stages in ductile rupture*” en “Application to crack initiation and stable crack growth, three dimensional constitutive relations and ductile fracture”, Ed. S. Nemeth-Nasser, S. North Holland Publishing Company, p. 185-205 (1981).
- [62] Rice, J.R. y Tracey, D.M., “*On the Ductile Enlargement of Voids in Triaxial Stress Fields*”, J. Mech. Phys. Solids, Vol. 17, p. 201-217 (1969).
- [63] Gurson, A.L., “*Continuum Theory of Ductile Rupture by Void Nucleation and Growth. Part I: Yield Criteria and Flow Rules for Porous Ductile Materials*”, J. Eng. Mat. Tech., Vol. 99, p. 2-15 (1997).
- [64] Tvergaard, V., “*Influence of Voids on Shear Band Instabilities Under Plane Strain Conditions*”, Int. J. Fracture, Vol. 17, p. 389-407 (1981).
- [65] Tvergaard, V., “*On Localization in Ductile Materials Containing Spherical Voids*”, Int. J. Fracture, Vol. 18, p. 237-252 (1982).
- [66] Lorentz, E., Wadier, Y., Debruyne, G., “*Mécanique de la Rupture en Présence de Plasticité: Définition d'un Taux de Restitution d'énergie*”, CRAS. t. 328, série IIb (2000).

- [67] Marie, S., “*Approche Énergétique de la Déchirure Ductile*”, Tesis doctoral de la Universidad de Poitiers, Francia (1999).
- [68] Marie, S., Chapuliot, S. y Bezine, G., “*A New Energetic Approach to Model Ductile Tearing for Real Components*”, Proceedings of PVP99 conference, Boston, USA (1999).
- [69] Marie, S. y Chapuliot, S., “*2D Crack Growth Simulation with an Energetic Approach*”, Nuclear Engineering and Design, Vol. 212, Issues 1-3, p. 851-863 (2002).
- [70] Debruyne, G., “*Proposition d'un Paramètre Énergétique de Rupture pour les Matériaux Dissipatifs*”, CRAS. t. 328, série IIb (2000).
- [71] Watanabe, K., “*New Proposal of Crack Energy Density Concept as a Fundamental Fracture Mechanics Parameter*”, Bull. JSME, p. 24-198 (1981).
- [72] Pellisier-Tanon, A. et al., “*Transferability of Data from Specimens to Structures for Defect Assessment on LWR Components*”, Draft Final Report, EER DC 1368 (1998).
- [73] Brocks, W., Schmitt, W., “*The Second Parameter in J-R curves: Constraint or Triaxiality*”. Constraint Effects in Fracture Theory and Application: 2nd Volume, ASTM STP 1244, American Society for Testing Materials, p. 232-252, Philadelphia.
- [74] Wallin, K., “*The Scatter in K_{IC} Results*” Engineering Fracture Mechanics, Vol. 19, p. 1085-1093 (1984).
- [75] Wallin, K., “*The Size Effect in K_{IC} Results*”, Eng. Fract. Mech., Vol. 22, p. 149-163 (1985).
- [76] Wallin, K., “*Statistical Re-evaluation of the ASME K_{IC} and K_{IR} Fracture Toughness Reference Curves*”, Nuclear Eng. Design, Vol. 193, p. 317-326 (1999).
- [77] Brückner, A., Munz, D. “*Prediction of Failure Probabilities for Cleavage Fracture from the Scatter of Crack Geometry and of Fracture Toughness Using the Weakest Link Model*”, Eng. Fract. Mech., Vol. 18, p. 359-375 (1983).

- [78] Slatcher, S., Evandt, Ø. “*Practical Application of the Weakest-link Model to Fracture Toughness Problems*”, Eng. Fract. Mech., Vol. 24, p. 495-508 (1986).
- [79] Minami, F., Toyoda, M., Satoh, K., “*A Probabilistic Analysis on Thickness Effect in Fracture Toughness*”, Eng. Fract. Mech., Vol. 23, p. 433-444 (1987).
- [80] ASTM E-1921, “*Test Method for Determination of Reference Temperature, T_0 , for Ferritic Steels in the Transition Range*”, American Society for Testing and Materials, Philadelphia (1998).
- [81] Natishan, M.E. y Kirk, M.T., “*A Micro-mechanical Evaluation of the Master Curve*”, Fatigue and Fracture Mechanics: 30th Volume, ASTM STP 1360, American Society for Testing and Materials, p. 51-60, West Conshohocken (2000).
- [82] Ritchie, R.O., Knott, J.F. y Rice, J.R., “*On the Relationship between Critical Tensile Stress and Fracture Toughness in Mild Steel*”, J. Mech. Phys. Solids, Vol. 21, p. 395-410 (1973).
- [83] Rousselier, G., “*Ductile fracture models and their potential in local approach of fracture*”, Nuclear Engineering and Design, Vol. 105, p. 97-111 (1987).
- [84] Alegre, J.M. “*Estudio Mediante Técnicas de Aproximación Local de la Fractura de Aceros Inoxidables Austeno-Ferríticos Envejecidos*”, Tesis Doctoral, Universidad de Cantabria (2000)
- [85] Kishimoto, K., Takeuchi, N., Auki, S., Sakata, M. “*Computational accuracy of the - integral by the finite-element method*”, International Journal of Pressure Vessels and Piping, Vol. 44, Issue 2, p. 255-266 (1990)
- [86] Francfort, G. y Marigo, J.J., “*Revisiting Brittle Fracture as an Energy Minimisation Problem*”, J. Mech. Phys. Sol., Vol. 46, nº8, p. 1319-1342 (1998).
- [87] Lin, G., Cor nec, A. y Schwalbe, K.H., “*Three-dimensional Finite Element Simulation of Crack Extension in Aluminium Alloy 2024FC*”, Fatigue and Fracture Engineering Materials and Structures, Vol. 21, p. 1159-1173 (1998).

- [88] Elices, M., Guinea, G.V., Gómez, J., Planas, J., “*The Cohesive Zone Model: advantages, limitations and challenges*”, Engineering Fracture Mechanics, Vol.70, Issue 14, p. 1913-1927 (2003)
- [89] Brocks, W., “*Modelling of Crack Growth in Sheet Metal*”, Proceedings of ICES-2K, Los Angeles (2000).
- [90] Álvarez, J.A., “*Fisuración Inducida por Hidrógeno de Aceros Soldables Microaleados: Caracterización y Modelo de Comportamiento*”, Tesis Doctoral, Universidad de Cantabria (1998)
- [91] Brickstad, B., Bergman, M., Andersson, P., Dahlberg, L., Sattari-Far, I. y Nilsson, F., “*Procedures Used in Sweden for Safety Assessment of Components with Cracks*”, Int. J. Pressure Vessels and Piping, Vol. 77, p. 877-881 (2000).
- [92] RSE-M Code, “*Rules for In-service Inspection of Nuclear Power Plant Components*”, 1997 Edition + 1998 and 2000 Addenda, AFCEN, Paris.
- [93] Sherry, A.H., Wilkes, M.A., Beardsmore, D.W. y Lidbury, D., “*Material Constraint Parameters for the Assessment of Shallow Defects in Structural Components- Part I: Parameter Solutions*”, Engineering Fracture Mechanics, Vol. 72, Issue 15, p. 2373-2395, (2005).
- [94] Wallin, K., “*Quantifying T_{stress} Controlled Constraint by the Master Curve Transition Temperature T_0* ”, Engineering Fracture Mechanics, Vol. 68, p. 303-328 (2001).
- [95] Smith, E., “*A Comparison of Mode I and Mode III Results for the Elastic Stress Distribution in the Immediate Vicinity of a Blunt Notch*”, International Journal of Engineering Science 42, p. 473-481, (2004)
- [96] Pluvinage, G., “*Fatigue and Fracture Emanating from Notch; the Use of the Notch Stress Intensity Factor*”, Nuclear Engineering and Design 185, p.173-184, (1998)
- [97] Timoshenko, S., Goodier, J.N., *Theory of Elasticity*. McGraw-Hill, New York (1951).
- [98] Neuber, N., Weiss, V., Trans. ASME paper No. 62-WA-270 (1962).

- [99] Chen, C.C., Pan, H.I., “*Collection of Papers on Fracture of Metals*”. Metallurgy Industry Press, Beijing, p. 197-219 (1978).
- [100] Usami, S.I., Tanaka, Jono, M., Komai, k., “*Current Research on Fatigue Cracks*”, The Society of Materials Science, Kyoto, Japan, 119 (1985).
- [101] Glinka, G., Newport, A., Int. J. Fatigue 9, 143 (1987).
- [102] Kujawski, D., “*Estimation of Stress Intensity Factors for Small Cracks at Notches*”, Fatigue Fract. Eng. Mater. Struct. 14, p. 953-965 (1991).
- [103] Bhattacharya, S., Kumar, A.N., “*Rotational Factor Using Bending Moment Approach Under Elasto-plastic Situation in 3PB Notch Geometry*”, Engineering Fracture Mechanics 50, p. 495-505 (1995).
- [104] Niu, L.S., Chehimi, C., Pluvinage, G., “*Stress Field Near a Large Blunted V Notch and Application of the Concept of Critical Notch Stress Intensity Factor to the Fracture of Very Brittle Materials*”, Engineering Fracture Mechanics 49 (3), p. 325-335 (1994).
- [105] Bao, Y., Jin, Z., Fatigue Fract. Eng. Mater. Struct. 16, 829 (1993).
- [106] Fenghui, W., Journal of Material Science 35, 2543 (2000).
- [107] Creager, M., Paris, C., “*Elastic Field Equations for Blunt Cracks with Reference to Stress Corrosion Cracking*”, International Journal of Fracture 3, p. 247-252, (1967).
- [108] Yates, J.R. y Brown, M.W., “*Prediction of the Length of non Propagating Fatigue Cracks*”, Fatigue and Fracture Engineering Materials and Structures, Vol. 10, p. 187-201 (1987).
- [109] Elayachi, I., Pluvinage, G., Bensalah, M.O., Lebienvenu, M., Dlouhy, I., “*To Joint Effect of Temperature and Notch Root Radius on Fracture Toughness*”, Engineering Mechanics, Vol.12, nº1, p. 11-22, (2005).
- [110] Akourri, O., Louah, M., Kifani, A., Gilgert, G., Pluvinage, G., “*The Effect of Notch Radius on Fracture Toughness J_{lc}* ”, Engineering Fracture Mechanics 65, p. 491-505, (2000).

- [111] Yoda, M., “*The Effect of the Notch Root Radius on the J-Integral Fracture Toughness Under Modes I, II and III Loadings*”, Engineering Fracture Mechanics 26, No. 3, p. 425-431 (1987).
- [112] Veidt, M., Schindler, H.J., “*On the Effect of Notch Radius and Local Friction on the Mode I and Mode II Fracture Toughness of a High-strength Steel*”, Engineering Fracture Mechanics 58, No. 3, p. 223-231,(1997).
- [113] Yokobori, T., Konosu, S., “*Effects of Ferrite Grain Size, Notch Acuity and Notch Length on Brittle Fracture Stress of Notched Specimens of Low Carbon Steel*”, Engineering Fracture Mechanics 9, p. 839-847 (1977).
- [114] Spink, G.M., Worthington, P.J., Heald, P.T., “*The Effect of Notch Acuity on Fracture Toughness Testing*”, Materials Science and Engineering 11, p. 113-117 (1973).
- [115] Zhang, J.P., Venugopalan, D., “*Effects of Notch Radius and Anisotropy on the Crack Tip Plastic Zone*”, Engineering Fracture Mechanics 26, No. 6, p. 913-925 (1987).
- [116] BS EN 10025-1:2004, “*Hot Rolled Products of Non-alloy Structural Steels. General Delivery Conditions*”, British Standard (2004).
- [117] BS EN 10002-1:2001, “*Tensile Testing of Metallic Materials. Method of Test at Ambient Temperature*”, British Standard (2001).
- [118] BS 7448: Part 1, “*Fracture Mechanics Toughness Tests. Part 1. Method for Determination of K_{IC} , Critical CTOD and Critical J Values of Metallic Materials*” British Standard (1991).
- [119] ASTM E 647, “*Standard Test Method for Measurement of Fatigue Crack Growth Rates*”, American Society for Testing and Materials, Philadelphia (1997)
- [120] Horn, A.J., “*The Effect of Notch Acuity on Structural Integrity*”, CORUS STC/TRA SIN/CR/7043/2004/R (2005).
- [121] Sherry, A.H., Lidbury, D.P.G., Bass, B.R. and Williams, P.T., “*Developments in Local Approach Methodology with Application to the Analysis/Reanalysis of the NESC-1 PTS*

- Benchmark Equipment*", International Journal of Pressure Vessels and Piping, 78 Issues 2-3, p. 237-249 (2001).
- [122] Gao, X., Ruggieri, C., Dodds, R.H.Jr, "*Calibration of Weibull Stress Parameters Using Fracture Toughness Data*", International Journal of Fracture, 92, nº2, p. 175-200 (1998).
- [123] Minami, F. et al, "*Method of Constraint Loss Correction of CTOD Fracture Toughness for Fracture Assessment of Steel Components*", Proceedings of the International Conference on Fitness-for-Service FITNET 2006, nº 33, Amsterdam (2006)
- [124] O'Dowd, N.P., "*Application of Two Parameter Approaches in Elastic-plastic Fracture Mechanics*", Engineering Fracture Mechanics 52, Nº3, p. 445-465, (1995).
- [125] Sherry, A.H., France, C.C, Goldthorpe, M.R., "*Compendium of T-stress Solutions for Two and Three Dimensional Cracked Geometries*", Fatigue and Fracture of Engineering Materials and Structures, Vo. 18, Nº1, p. 141-155, (1995).