

Acknowledgements

I would like to thank T.O. Niinikoski for all the time and energy he has dedicated to the supervision of this project. This thesis work is a mirror of his ideas and a tribute to his unconditional support. He has allowed me to have a good dose of exposure through presentations in several forums and publications. I hope the result itself can express my sincere gratitude to him.

This doctoral work would have never been carried out without the encouragement of F. Calviño, who gave me the opportunity of preparing the work in collaboration with the Universtitat Politècnica de Catalunya.

W. Kienzle, K. Eggert and G. Matthia supported the common project between RD39 Collaboration and TOTEM for the development of edgeless silicon detectors for luminosity measurement at LHC.

S. Grohmann measured the heat transfer coefficient in two-phase flow in micropipes, which have been used for the cryogenic detector module design. The thermal tests on the mechanical module would have never been carried out without his help. Thanks for showing always a persistent and professional attitude in our common work.

Despite this work has been carried out within a rather small team, it has received the advice and expertise of many scientific and technical professionals working at different fields at CERN, to whom I am indebted:

The Cryolab staff, J.M. Rieubland, G. Vandoni, A. Vacca, L. Dufay, J. Gay, L. le Mao, S. Prunet, G. Ratcliffe and H. Vigier participated in the measurement of the integral thermal dilatation of filled epoxies and the machining of the test beam cryostat. G. Nuessle collaborated in the module thermal tests performance and analysis, and in the test beam cryostat instrumentation and tests with liquid nitrogen.

R. Fortin supervised the design of the precision assembly tooling. N. Buil took care of the machining of the assembly tooling, support posts, epoxy samples and test beam cryostat at the CERN Central Workshop.

C. Joram provided the space to install a module assembly laboratory and offered the use of bonding facilities. J.M. Avondo, I. Mc.Gill and F. Cossey bonded the modules with large sensors and prepared the edgeless pair of diodes samples for beam tests.

A. Braem, C. David and D. Fraissard provided laboratory space, equipment and shared their expertise when preparing the filled epoxy samples. M.L. Delsante, Y. Forestier, C. Hauviller, R. Macías, A. Perrin and S. Sgobba did the measurements of the mechanical properties of filled epoxies and shared their knowledge on composite materials. A. Folley prepared the carbon fiber composite spacers. We held discussions with M. Oriunno and B. Calcagno on finite element simulations.

A. Cattai, A. Honma and G. Rolandi provided the CMS ceramic hybrids and shared interesting discussions on the CMS tracker module design. P. Luukka, O. Militaru and X. Rouby prepared the software to characterize the hybrids and collaborated in the performance and analysis of the low temperature hybrid tests. A. Marchioro and W. Beaumont were always ready to hear our problems

related to the operation of the readout electronics at low temperature and provided the right hints to go on with the tests. The fabrication and mounting of electronic components, feedthroughs and edgeless diode mother boards were done by C. Millerin, R. de Oliveira and N. Wauquier.

The processing and cutting of the edgeless pair of diodes was done by Z. Li at BNL. V. Avati, L. Casagrande, V. Granata, E. Grioriev, E. Heijne, S. Klauke, P. Rato and P. Sousa participated in the test beam setup preparation. L. Mirabito, P. Siegrist and B. Trocmé dedicated a lot of their beam time to acquire data with the CMS tracker using the edgeless diode as a trigger. L. Silvestris and T. Boccali gave me access to the ORCA software, and helped me in the track reconstruction. J. Rico participated in the edgeless silicon sensor analysis and discussion of the results. V. Karimäki helped us clarify the statistics involved in the linear fits. L. Gatignon helped us to understand the X5 beam. J. Härkönen processed the silicon microstrip detector, the pitch adapter and the support plate at the Microelectronics Center of Helsinki University of Technology. Many aspects of semiconductor physics became clear to me thanks to the many discussions with J. Lozano.

I am in thankful to all of you.

L. Guy, S. Stenhammar and the Ensemble Vocal Séquence filled these years with music. Thanks to Jérôme and to my family for their tangible and intangible support in the preparation of this Ph.D. work. Thanks for your patience.

Acknowledgements

I would like to thank T.O. Niinikoski for all the time and energy he has dedicated to the supervision of this project. This thesis work is a mirror of his ideas and a tribute to his unconditional support. He has allowed me to have a good dose of exposure through presentations in several forums and publications. I hope the result itself can express my sincere gratitude to him.

This doctoral work would have never been carried out without the encouragement of F. Calviño, who gave me the opportunity of preparing the work in collaboration with the Universtitat Politècnica de Catalunya.

W. Kienzle, K. Eggert and G. Matthia supported the common project between RD39 Collaboration and TOTEM for the development of edgeless silicon detectors for luminosity measurement at LHC.

S. Grohmann measured the heat transfer coefficient in two-phase flow in micropipes, which have been used for the cryogenic detector module design. The thermal tests on the mechanical module would have never been carried out without his help. Thanks for showing always a persistent and professional attitude in our common work.

Despite this work has been carried out within a rather small team, it has received the advice and expertise of many scientific and technical professionals working at different fields at CERN, to whom I am indebted:

The Cryolab staff, J.M. Rieubland, G. Vandoni, A. Vacca, L. Dufay, J. Gay, L. le Mao, S. Prunet, G. Ratcliffe and H. Vigier participated in the measurement of the integral thermal dilatation of filled epoxies and the machining of the test beam cryostat. G. Nuessle collaborated in the module thermal tests performance and analysis, and in the test beam cryostat instrumentation and tests with liquid nitrogen.

R. Fortin supervised the design of the precision assembly tooling. N. Buil took care of the machining of the assembly tooling, support posts, epoxy samples and test beam cryostat at the CERN Central Workshop.

C. Joram provided the space to install a module assembly laboratory and offered the use of bonding facilities. J.M. Avondo, I. Mc.Gill and F. Cossey bonded the modules with large sensors and prepared the edgeless pair of diodes samples for beam tests.

A. Braem, C. David and D. Fraissard provided laboratory space, equipment and shared their expertise when preparing the filled epoxy samples. M.L. Delsante, Y. Forestier, C. Hauviller, R. Macías, A. Perrin and S. Sgobba did the measurements of the mechanical properties of filled epoxies and shared their knowledge on composite materials. A. Folley prepared the carbon fiber composite spacers. We held discussions with M. Oriunno and B. Calcagno on finite element simulations.

A. Cattai, A. Honma and G. Rolandi provided the CMS ceramic hybrids and shared interesting discussions on the CMS tracker module design. P. Luukka, O. Militaru and X. Rouby prepared the software to characterize the hybrids and collaborated in the performance and analysis of the low temperature hybrid tests. A. Marchioro and W. Beaumont were always ready to hear our problems

related to the operation of the readout electronics at low temperature and provided the right hints to go on with the tests. The fabrication and mounting of electronic components, feedthroughs and edgeless diode mother boards were done by C. Millerin, R. de Oliveira and N. Wauquier.

The processing and cutting of the edgeless pair of diodes was done by Z. Li at BNL. V. Avati, L. Casagrande, V. Granata, E. Grioriev, E. Heijne, S. Klauke, P. Rato and P. Sousa participated in the test beam setup preparation. L. Mirabito, P. Siegrist and B. Trocmé dedicated a lot of their beam time to acquire data with the CMS tracker using the edgeless diode as a trigger. L. Silvestris and T. Boccali gave me access to the ORCA software, and helped me in the track reconstruction. J. Rico participated in the edgeless silicon sensor analysis and discussion of the results. V. Karimäki helped us clarify the statistics involved in the linear fits. L. Gatignon helped us to understand the X5 beam. J. Härkönen processed the silicon microstrip detector, the pitch adapter and the support plate at the Microelectronics Center of Helsinki University of Technology. Many aspects of semiconductor physics became clear to me thanks to the many discussions with J. Lozano.

I am in thankful to all of you.

L. Guy, S. Stenhammar and the Ensemble Vocal Séquence filled these years with music. Thanks to Jérôme and to my family for their tangible and intangible support in the preparation of this Ph.D. work. Thanks for your patience.

Acknowledgements

I would like to thank T.O. Niinikoski for all the time and energy he has dedicated to the supervision of this project. This thesis work is a mirror of his ideas and a tribute to his unconditional support. He has allowed me to have a good dose of exposure through presentations in several forums and publications. I hope the result itself can express my sincere gratitude to him.

This doctoral work would have never been carried out without the encouragement of F. Calviño, who gave me the opportunity of preparing the work in collaboration with the Universitat Politècnica de Catalunya.

W. Kienzle, K. Eggert and G. Matthia supported the common project between RD39 Collaboration and TOTEM for the development of edgeless silicon detectors for luminosity measurement at LHC.

S. Grohmann measured the heat transfer coefficient in two-phase flow in micropipes, which have been used for the cryogenic detector module design. The thermal tests on the mechanical module would have never been carried out without his help. Thanks for showing always a persistent and professional attitude in our common work.

Despite this work has been carried out within a rather small team, it has received the advice and expertise of many scientific and technical professionals working at different fields at CERN, to whom I am indebted:

The Cryolab staff, J.M. Rieubland, G. Vandoni, A. Vacca, L. Dufay, J. Gay, L. le Mao, S. Prunet, G. Ratcliffe and H. Vigier participated in the measurement of the integral thermal dilatation of filled epoxies and the machining of the test beam cryostat. G. Nuessle collaborated in the module thermal tests performance and analysis, and in the test beam cryostat instrumentation and tests with liquid nitrogen.

R. Fortin supervised the design of the precision assembly tooling. N. Buil took care of the machining of the assembly tooling, support posts, epoxy samples and test beam cryostat at the CERN Central Workshop.

C. Joram provided the space to install a module assembly laboratory and offered the use of bonding facilities. J.M. Avondo, I. Mc.Gill and F. Cossey bonded the modules with large sensors and prepared the edgeless pair of diodes samples for beam tests.

A. Braem, C. David and D. Fraissard provided laboratory space, equipment and shared their expertise when preparing the filled epoxy samples. M.L. Delsante, Y. Forestier, C. Hauviller, R. Macías, A. Perrin and S. Sgobba did the measurements of the mechanical properties of filled epoxies and shared their knowledge on composite materials. A. Folley prepared the carbon fiber composite spacers. We held discussions with M. Oriunno and B. Calcagno on finite element simulations.

A. Cattai, A. Honma and G. Rolandi provided the CMS ceramic hybrids and shared interesting discussions on the CMS tracker module design. P. Luukka, O. Militaru and X. Rouby prepared the software to characterize the hybrids and collaborated in the performance and analysis of the low temperature hybrid tests. A. Marchioro and W. Beaumont were always ready to hear our problems

related to the operation of the readout electronics at low temperature and provided the right hints to go on with the tests. The fabrication and mounting of electronic components, feedthroughs and edgeless diode mother boards were done by C. Millerin, R. de Oliveira and N. Wauquier.

The processing and cutting of the edgeless pair of diodes was done by Z. Li at BNL. V. Avati, L. Casagrande, V. Granata, E. Grioriev, E. Heijne, S. Klauke, P. Rato and P. Sousa participated in the test beam setup preparation. L. Mirabito, P. Siegrist and B. Trocmé dedicated a lot of their beam time to acquire data with the CMS tracker using the edgeless diode as a trigger. L. Silvestris and T. Boccali gave me access to the ORCA software, and helped me in the track reconstruction. J. Rico participated in the edgeless silicon sensor analysis and discussion of the results. V. Karimäki helped us clarify the statistics involved in the linear fits. L. Gatignon helped us to understand the X5 beam. J. Härkönen processed the silicon microstrip detector, the pitch adapter and the support plate at the Microelectronics Center of Helsinki University of Technology. Many aspects of semiconductor physics became clear to me thanks to the many discussions with J. Lozano.

I am in thankful to all of you.

L. Guy, S. Stenhammar and the Ensemble Vocal Séquence filled these years with music. Thanks to Jérôme and to my family for their tangible and intangible support in the preparation of this Ph.D. work. Thanks for your patience.

Acknowledgements

I would like to thank T.O. Niinikoski for all the time and energy he has dedicated to the supervision of this project. This thesis work is a mirror of his ideas and a tribute to his unconditional support. He has allowed me to have a good dose of exposure through presentations in several forums and publications. I hope the result itself can express my sincere gratitude to him.

This doctoral work would have never been carried out without the encouragement of F. Calviño, who gave me the opportunity of preparing the work in collaboration with the Universitat Politècnica de Catalunya.

W. Kienzle, K. Eggert and G. Matthia supported the common project between RD39 Collaboration and TOTEM for the development of edgeless silicon detectors for luminosity measurement at LHC.

S. Grohmann measured the heat transfer coefficient in two-phase flow in micropipes, which have been used for the cryogenic detector module design. The thermal tests on the mechanical module would have never been carried out without his help. Thanks for showing always a persistent and professional attitude in our common work.

Despite this work has been carried out within a rather small team, it has received the advice and expertise of many scientific and technical professionals working at different fields at CERN, to whom I am indebted:

The Cryolab staff, J.M. Rieubland, G. Vandoni, A. Vacca, L. Dufay, J. Gay, L. le Mao, S. Prunet, G. Ratcliffe and H. Vigier participated in the measurement of the integral thermal dilatation of filled epoxies and the machining of the test beam cryostat. G. Nuessle collaborated in the module thermal tests performance and analysis, and in the test beam cryostat instrumentation and tests with liquid nitrogen.

R. Fortin supervised the design of the precision assembly tooling. N. Buil took care of the machining of the assembly tooling, support posts, epoxy samples and test beam cryostat at the CERN Central Workshop.

C. Joram provided the space to install a module assembly laboratory and offered the use of bonding facilities. J.M. Avondo, I. Mc.Gill and F. Cossey bonded the modules with large sensors and prepared the edgeless pair of diodes samples for beam tests.

A. Braem, C. David and D. Fraissard provided laboratory space, equipment and shared their expertise when preparing the filled epoxy samples. M.L. Delsante, Y. Forestier, C. Hauviller, R. Macías, A. Perrin and S. Sgobba did the measurements of the mechanical properties of filled epoxies and shared their knowledge on composite materials. A. Folley prepared the carbon fiber composite spacers. We held discussions with M. Oriunno and B. Calcagno on finite element simulations.

A. Cattai, A. Honma and G. Rolandi provided the CMS ceramic hybrids and shared interesting discussions on the CMS tracker module design. P. Luukka, O. Militaru and X. Rouby prepared the software to characterize the hybrids and collaborated in the performance and analysis of the low temperature hybrid tests. A. Marchioro and W. Beaumont were always ready to hear our problems

related to the operation of the readout electronics at low temperature and provided the right hints to go on with the tests. The fabrication and mounting of electronic components, feedthroughs and edgeless diode mother boards were done by C. Millerin, R. de Oliveira and N. Wauquier.

The processing and cutting of the edgeless pair of diodes was done by Z. Li at BNL. V. Avati, L. Casagrande, V. Granata, E. Grioriev, E. Heijne, S. Klauke, P. Rato and P. Sousa participated in the test beam setup preparation. L. Mirabito, P. Siegrist and B. Trocmé dedicated a lot of their beam time to acquire data with the CMS tracker using the edgeless diode as a trigger. L. Silvestris and T. Boccali gave me access to the ORCA software, and helped me in the track reconstruction. J. Rico participated in the edgeless silicon sensor analysis and discussion of the results. V. Karimäki helped us clarify the statistics involved in the linear fits. L. Gatignon helped us to understand the X5 beam. J. Härkönen processed the silicon microstrip detector, the pitch adapter and the support plate at the Microelectronics Center of Helsinki University of Technology. Many aspects of semiconductor physics became clear to me thanks to the many discussions with J. Lozano.

I am in thankful to all of you.

L. Guy, S. Stenhammar and the Ensemble Vocal Séquence filled these years with music. Thanks to Jérôme and to my family for their tangible and intangible support in the preparation of this Ph.D. work. Thanks for your patience.

Acknowledgements

I would like to thank T.O. Niinikoski for all the time and energy he has dedicated to the supervision of this project. This thesis work is a mirror of his ideas and a tribute to his unconditional support. He has allowed me to have a good dose of exposure through presentations in several forums and publications. I hope the result itself can express my sincere gratitude to him.

This doctoral work would have never been carried out without the encouragement of F. Calviño, who gave me the opportunity of preparing the work in collaboration with the Universitat Politècnica de Catalunya.

W. Kienzle, K. Eggert and G. Matthia supported the common project between RD39 Collaboration and TOTEM for the development of edgeless silicon detectors for luminosity measurement at LHC.

S. Grohmann measured the heat transfer coefficient in two-phase flow in micropipes, which have been used for the cryogenic detector module design. The thermal tests on the mechanical module would have never been carried out without his help. Thanks for showing always a persistent and professional attitude in our common work.

Despite this work has been carried out within a rather small team, it has received the advice and expertise of many scientific and technical professionals working at different fields at CERN, to whom I am indebted:

The Cryolab staff, J.M. Rieubland, G. Vandoni, A. Vacca, L. Dufay, J. Gay, L. le Mao, S. Prunet, G. Ratcliffe and H. Vigier participated in the measurement of the integral thermal dilatation of filled epoxies and the machining of the test beam cryostat. G. Nuessle collaborated in the module thermal tests performance and analysis, and in the test beam cryostat instrumentation and tests with liquid nitrogen.

R. Fortin supervised the design of the precision assembly tooling. N. Buil took care of the machining of the assembly tooling, support posts, epoxy samples and test beam cryostat at the CERN Central Workshop.

C. Joram provided the space to install a module assembly laboratory and offered the use of bonding facilities. J.M. Avondo, I. Mc.Gill and F. Cossey bonded the modules with large sensors and prepared the edgeless pair of diodes samples for beam tests.

A. Braem, C. David and D. Fraissard provided laboratory space, equipment and shared their expertise when preparing the filled epoxy samples. M.L. Delsante, Y. Forestier, C. Hauviller, R. Macías, A. Perrin and S. Sgobba did the measurements of the mechanical properties of filled epoxies and shared their knowledge on composite materials. A. Folley prepared the carbon fiber composite spacers. We held discussions with M. Oriunno and B. Calcagno on finite element simulations.

A. Cattai, A. Honma and G. Rolandi provided the CMS ceramic hybrids and shared interesting discussions on the CMS tracker module design. P. Luukka, O. Militaru and X. Rouby prepared the software to characterize the hybrids and collaborated in the performance and analysis of the low temperature hybrid tests. A. Marchioro and W. Beaumont were always ready to hear our problems

related to the operation of the readout electronics at low temperature and provided the right hints to go on with the tests. The fabrication and mounting of electronic components, feedthroughs and edgeless diode mother boards were done by C. Millerin, R. de Oliveira and N. Wauquier.

The processing and cutting of the edgeless pair of diodes was done by Z. Li at BNL. V. Avati, L. Casagrande, V. Granata, E. Grioriev, E. Heijne, S. Klauke, P. Rato and P. Sousa participated in the test beam setup preparation. L. Mirabito, P. Siegrist and B. Trocmé dedicated a lot of their beam time to acquire data with the CMS tracker using the edgeless diode as a trigger. L. Silvestris and T. Boccali gave me access to the ORCA software, and helped me in the track reconstruction. J. Rico participated in the edgeless silicon sensor analysis and discussion of the results. V. Karimäki helped us clarify the statistics involved in the linear fits. L. Gatignon helped us to understand the X5 beam. J. Härkönen processed the silicon microstrip detector, the pitch adapter and the support plate at the Microelectronics Center of Helsinki University of Technology. Many aspects of semiconductor physics became clear to me thanks to the many discussions with J. Lozano.

I am in thankful to all of you.

L. Guy, S. Stenhammar and the Ensemble Vocal Séquence filled these years with music. Thanks to Jérôme and to my family for their tangible and intangible support in the preparation of this Ph.D. work. Thanks for your patience.