

9 BIBLIOGRAFIA

Adelberg, M. (1967) Breakup rate and penetration of a liquid jet in a gas stream. *AIAA J.* (5), pp. 1408-1415

Adewuyi, Y.G.; Carmichael, G.R. (1982) A theoretical investigation of gaseous absorption by water droplets from SO₂ - HNO₃ - NH₃ - CO₂ - HCl mixtures. *Atm. Env.* 16, (4), pp. 719-729

Allen, R.W.K. (1996) Prediction of venturi scrubber grade efficiency curves using the contacting power law. *Powder Technol.* (86), pp. 137-144

Allen, R.W.K.; Van Santen, A. (1996) Designing for pressure drop in venturi scrubbers: the importance of dry pressure drop. *Chem. Eng. J.* (61), pp. 203-211

Alonso Fernández, D. (2000) *Experimental study of hydrodynamics in laboratory-scale venturi scrubbers with two different types of liquid injection*. PhD Thesis. University of Nottingham

Amenós, A.; Peñalver, A.; Toldrà, L.X. (1996) *Els drets del medi ambient*. Edicions El Mèdol. Tarragona

Ananthanarayanan, N.V.; Viswanathan, S. (1998) Estimatig maximum removal efficiency in venturi scrubbers. *AIChE J.* 44, (11), pp. 2549-2560

Ananthanarayanan, N.V.; Viswanathan, S. (1999) Predicting the liquid flux distribution and collection efficiency in cylindrical venturi scrubbers. *Ind. Eng. Chem. Res.* 38, (1), pp. 223-232

Ananthanarayanan, N.V.; Viswanathan, S. (1999) Effect of nozzle arrangement on venturi scrubber performance. *Ind. Eng. Chem. Res.* 38, (12), pp. 4889-4900.

Andreussi, P. (1983) Droplet transfer in two-phase annular flow. *Int. J. Multiphase Flow.* 9, (6), pp. 697-713

Andreussi, P.; Azzopardi, B.J. (1983) Droplet deposition and interchange in annular two-phase flow. *Int. J. Multiphase Flow.* 9, (6), pp. 681-695

Astarita, G. (1983) *Gas treating with chemical solvents* John Wiley & Sons. New York.

Astarita, G.; Gioia, F. (1964) Hydrogen sulphide chemical absorption. *Chem. Eng. Sci.* (19), pp. 963-971

Atay, I.; Lewandowski, G.; Trattner, R. (1987) Fluid flow and gas absorption in an ejector venturi scrubber. *Environmental Progress.* 6, (3), pp. 198-203

Atkinson, D.S.F.; Strauss, W. (1978) Droplet size and surface tension in venturi scrubbers. *J. Air Pollution Control Assoc.* 28, (11), pp. 1114-1118

Azzopardi, B.J. (1979) Measurements of drop sizes. *Int. J. Heat Mass Transfer.* (22), pp. 1245-1279

Azzopardi, B.J. (1992) Gas-liquid flows in cylindrical venturi scrubbers: boundary layer separation in the diffuser section. *Chem. Eng. Journal.* (49), pp. 55-64

Azzopardi, B.J. (1993) Liquid distribution in venturi scrubbers: the importance of liquid film in the channel walls. *Chem. Eng. Sci.* 48, (15), pp. 2807-2813

Azzopardi, B.J. (1997) Drops in annular two-phase flow. *Int. J. Multiphase Flow.* 23, (Suppl.), pp. 1-53

Azzopardi, B.J.; Freeman, G.; King, D.J. (1979) Drop sizes and deposition in annular two phase flow. *UKAEA Report*. AERE-R9711

Azzopardi, B.J.; Govan, A.H. (1984) The modelling of venturi scrubbers. *Filtration and Separation.* (21), pp. 196-200

Azzopardi, B.J.; Hills, J.H. (2000) Multiphase systems. University of Nottingham. (notes de classe)

Azzopardi, B.J.; Memory, S.B.; Smith, P.A. (1989) Experimental study of annular flow in a venturi. *4th International Conference on Physical Modelling of Multiphase Flow*. Coventry

Azzopardi, B.J.; Teixeira, S.F.C.F.; Govan, A.H.; Bott, T.R. (1991) An improved model for pressure drop in venturi scrubbers. *Trans IChemE B*. (69), pp. 55-64

Baboolal, L.B.; Pruppacher, H.R.; Topalian, J.H. (1981) A sensitivity study of a theoretical model of SO₂ scavenging by water drops in air. *J. Atm. Sci.* (38), pp. 856-870

Barnea, D.; Shoham, O.; Taitel, Y. (1982) Flow pattern transition for downward inclined two-phase flow: Horizontal to vertical. *Chem. Eng. Sci.* (37), pp. 735-740

Bayvel, L.P. (1982) The effect of polydispersity of drops on the efficiency of a venturi scrubber. *Trans. IChemE.* (60), pp. 31-34

Behie, S.W.; Beeckmans, J.M. (1974) Effects of water injection arrangement on the performance of a venturi scrubber. *J. Air Pollution Control Assoc.* 24, (10), pp. 943-945

Belhaj, S.; Guerin, P.; Limnios, N.; Zoulalian, A. (1983) Analyse énergétique de l'efficacité d'un absorbeur réactionnel du type venturi à jet. *Chem. Eng. J.* (26), pp. 21-32

Bhat, P.A.; Mitra, A.K.; Roy, A.N. (1972) Momentum transfer in a horizontal liquid jet ejector. *Canadian J. Chem. Eng.* (50), pp. 313-317

Bird, R.B.; Stewart, W.E.; Lightfoot, E.N. (1982) *Fenómenos de transporte*. Reverte. Barcelona

Boll, R.H (1973) Particle collection and pressure drop in venturi scrubbers. *Ind. Eng. Chem. Fundam.* (12), pp. 40-50

Boll, R.H.; Flais, L.R.; Mauerer, P.W.; Thompson, W.L. (1974) Mean drop size in a full scale venturi scrubber via transmissometer. *J. Air Pollution Control Assoc.* 24, (10), pp. 934-938

Box, G.E.P.; Hunter, W.G.; Hunter, J.S. (1989) *Estadística para investigadores*. Reverté. Barcelona

Box, G.E.P.; Wilson, K.G. (1951) On the experimental attainment of optimum conditions. *J. Royal Stat. Soc.* 13, (B), pp. 1-45

Boyadzhiev, K. (1964) On the optimal flow rate of liquid during chemisorption in a venturi tube. *Int. Chem. Eng.* 4, (1), pp. 22-26

Boyaval, S.; Dumouchel, C. (1998) The maximum entropy formalism and the determination of spray drop size distribution. *Proceedings ILASS - Europe 98*. pp. 1-6

Bravo Rodríguez, V.; Camacho Rubio, F.; Moya Vilar, M. (1991) Absorción de SO₂ en disoluciones de citrato monosódico. *Anales de Química*. 87, (3), pp. 363-370

Breña de la Rosa, A.; Wang, G.; Bachalo, W.D. (1992) The effect of swirl on the velocity and turbulence fields of a liquid spray. *J. Eng. Gas Turbines and Power*. (114), pp. 72-81

Briens, C.L.; Huynh, L.X.; Large, J.F.; Catros, A.; Bernard, J.R.; Bergognou, M.A. (1992) Hydrodynamics and gas-liquid mass transfer in a downward venturi-bubble column combination. *Chem. Eng. Sci.* 47, (13/14), pp. 3549-3556

Brink, J.A. Jr; Contant, C.E. (1958) Experiments on an industrial venturi scrubber. *Ind. Eng. Chem.* 50, (8), pp. 1157-1160

Broekhuis, R.R.; Koch, D.J.; Lynn, S (1992) A medium temperature process for removal of hydrogen sulfide from sour gas streams with aqueous metal sulfate solutions. *Ind. Eng. Chem. Res.* (31), pp. 2635-2642

Brogren, C.; Karlsson, H.T. (1997) Modeling the absorption of SO₂ in a spray scrubber using the penetration theory. *Chem. Eng. Sci.* 52, (18), pp. 3085-3099

Calvert, S. (1970) Venturi and other atomising scrubbers efficiency and pressure drop. *AIChE J.* 16, (3), pp. 392-396

Camacho Rubio, F.; Bravo Rodríguez, V.; Aguado Ramos, M. (1988) Absorción de SO₂ en disoluciones de acetato sódico. *Anales de Química.* 84, (3), pp. 355-361

Carmichael, G.R.; Peters, L.K. (1979) Some aspects of SO₂ absorption by water - generalized treatment. *Atmospheric Environment.* (13), pp. 1505-1513

Carvalho, I.S.; Heitor, M.V. (1998) Liquid film break-up in a model of a prefilming airblast nozzle. *Experiments in fluids.* (24), pp. 408-415

Chang, C.S.; Rochelle, G.T. (1981) SO₂ absorption into aqueous solutions. *AIChE J.* 27, (2), pp. 292-298

Chang, C.S.; Rochelle, G.T. (1982) Effect of organic acid additives on SO₂ absorption into CaO/CaCO₃ slurries. *AIChE J.* 28, (2), pp. 261-266

Chang, C.S.; Rochelle, G.T. (1985) SO₂ absorption into NaOH and Na₂SO₃ aqueous solutions. *Ind. Eng. Chem. Fundam.* 24, (1), pp. 7-11

Chapman, S.; Cowling, T.G. (1952) *The mathematical theory of non-uniform gases*. Cambridge University Press. Cambridge

Charpentier J.C. (1982) What's new in absorption with chemical reaction?. *Trans IChemE.* (60), pp. 131-156

Cheremisinoff, P.N. (1993) *Air pollution control and design for industry*. Marcel Dekker. New York

Cooney, D.O. (1985) Modeling venturi scrubber performance for H₂S removal from oil-shale retort gases. *Chem. Eng. Comm.* (35), pp. 315-338

Cooney, D.O.; Olsen, D.P. (1987) Absorption of SO₂ and H₂S in small-scale venturi scrubbers. *Chem. Eng. Comm.* (51), pp. 291-306

Cousin, J.; Yoon, S.J.; Dumouchel, C. (1996) Coupling of classical linear theory and maximum entropy formalism for prediction of drop size distribution in sprays: Application to pressure-swirl atomizers. *Atomization and Sprays.* 6, (5), pp. 601-622

Couto, H.S.; Carvalho, J.A.; Bastos-Netto, D. (1997) Theoretical formulation for Sauter mean diameter of pressure-swirl atomizers. *J. Propulsion and Power.* 13, (5), pp. 691-696

Cramers, P.H.M.R.; van Dierendonck, L.L.; Beenackers, A.A.C.M. (1992) Influence of the gas density on the gas entrainment rate and gas hold-up in loop-venturi reactors. *Chem. Eng. Sci.* 47, (9/11), pp. 2251-2256

Cramers, P.H.M.R.; Beenackers, A.A.C.M.; van Dierendonck, L.L. (1992) Hydrodynamics and mass transfer characteristics of a loop-venturi reactor with a downflow liquid jet ejector. *Chem. Eng. Sci.* 47, (13/14), pp. 3557-3564

Cramers, P.H.M.R.; Smit, L.; Leuteritz, G.M.; van Dierendonck, L.L.; Beenackers, A.A.C.M. (1993) Hydrodynamics and local mass transfer characteristics of gas-liquid ejectors. *Chem. Eng. J.* (53), pp. 67-73

Crank, J. (1975) *The mathematics of diffusion*. Oxford University Press. Oxford

Cunningham, R.G. (1957) Jet-pump theory and performance with fluids of high viscosity. *Transactions of the ASME.* (79), pp. 1807-1819

Cunningham, R.G. (1974) Gas compression with the liquid jet pump. *J. Fluids Eng.* (96), pp. 203-215

Cunningham, R.G. (1995) Liquid jet pumps for two-phase flows. *J. Fluids Eng.* (117), pp. 309-316

Dabir, B.; Riazi, M.R.; Davoudirad (1996) Modelling of falling film reactors. *Chem. Eng. Sci.* 51, (11), pp. 2553-2558

Danckwerts, P.V. (1951) Significance of liquid - film coefficients in gas absorption. *Ind. Eng. Chem.* 6, (43), pp. 1460

Danckwerts, P.V. (1970) *Gas - liquid reactions*. McGraw - Hill. New York

Davis, E.J.; van Ouwerkerk, M.; Venkatesh, S. (1979) An analysis of the falling film gas-liquid reactor. *Chem. Eng. Sci.* (34), pp. 539-550

Díaz González, F.; Limiñana de la Fe, G.; Rodríguez Sevilla, J. (1991) Absorción de SO₂ en disoluciones acuosas de Na₂SO₃ a bajas concentraciones de reactivos. *Anales de Química*. 87, (3), pp. 358-362

Dirix, C.A.M.C.; van der Wiele, K. (1990) Mass transfer in jet loop reactors. *Chem. Eng. Sci.* 45, (8), pp. 2333-2340

Dobre, M.; Bolle, L. (1998) Theoretical prediction of ultrasonic spray characteristics using the maximum entropy formalism. Proceedings *ILASS - Europe 98*. pp. 7-12

Dombrowski, N.; Johns, W.R. (1963) The aerodynamic instability and desintegration of viscous liquid sheets. *Chem. Eng. Sci.* 18, (2), pp. 203-214

Dumouchel, C.; Bloor, M.I.G.; Dombrowski, N.; Ingham, D.B.; Ledoux, M. (1993) Viscous flow in a swirl atomizer. *Chem. Eng. Sci.* 48, (1), pp. 81-87

Dutta, N.N.; Raghavan, K.V. (1987) Mass transfer and hydrodynamic characteristics of loop reactors with downflow liquid jet ejectors. *Chem. Eng. J.* (36), pp. 111-121

Dutta, B.K.; Hay, P.; Sutradhar, B.C. (1987) Comments on 'Modeling of a venturi scrubber for the control of gaseous pollutants'. *Ind. Eng. Chem. Res.* (26), pp. 1265

Ekman, F.O.; Johnstone, H.F. (1951) Collection of aerosols in a venturi scrubber. *Ind. Eng. Chem.* 46, (6), pp. 1358-1363

Elenkov, D.; Boyadzhiev, K. (1967) Hydrodynamics and mass transfer in a nozzleless venturi absorber. II Absorption of sulfur dioxide in water and aqueous solutions of surfactants. *Int. Chem. Eng.* 7, (2), pp. 191-193

Elger, D.F.; McLam, E.T.; Taylor, S.J. (1991) A new way to represent jet pump performance. *J. Fluids Eng.* (113), pp. 439-444

Elger, D.F.; Taylor, S.J.; Liou, C.P. (1994) Recirculation in an annular-type jet pump. *J. Fluids Eng.* (116), pp. 735-740

Empie, H.J.; Lien, S.J.; Yang, W.; Samuels, D.B. (1995) Effect of black liquor on droplet formation from commercial spray nozzles. *J. Pulp and Paper Sci.* 21, (2), pp. J63-J67

Fathikalajahi, J.; Talaie, M.R., Taheri, M. (1995) Theoretical study of liquid droplet dispersion in a venturi scrubber. *J. Air & Waste Manag. Assoc.* 45, pp. 181-185

Fathikalajahi, J.; Taheri, M.; Talaie, M.R. (1996) Theoretical study of nonuniform droplets concentration distribution on venturi scrubber performance. *Particulate Sci. Technol.* 14, pp. 153-164

Folsom, R.G. (1948) Jet pumps with liquid drive. *Chem. Eng. Progress.* 44, (10), pp. 765-770

Fore, L.B.; Dukler, A. E. (1995) Droplet deposition momentum transfer in annular flow. *AIChE J.* 41, (9), pp. 2040-2046

Frutos Cabanillas, G. (1992) Utilización del método de las superficies de respuesta en investigación farmacéutica. *An. Real Acad. Farm.* (58), pp. 295-316

Generalitat de Catalunya (1995) *Quaderns de medi ambient: La qualitat de l'aire a Catalunya, 1991-1994*. (4)

Glasscock, D.A.; Rochelle, G.T. (1989) Numerical simulation of theories for gas absorption with chemical reaction. *AIChE J.* 35, (8), pp. 1271-1281

Gosline, J.E.; O'Brien, M.P. (1934) The water jet pump. *University of California publications in engineering*. 3, (3), pp. 167-190

Grazzini, G.; Mariani, A. (1998) A simple program to design a multi-stage jet-pump for refrigeration cycles. *Energy Conversion and Management*. 39, (16-18), pp. 1827-1834

Gutiérrez-González, J.; Mans-Teixidó, C.; Costa-López, J. (1988) Improved mathematical model for a falling film sulfonation reactor. *Ind. Eng. Chem. Res.* (27), pp. 1701-1707

Haller, H.; Muschelknautz, E.; Schultz, T. (1989) Venturi scrubber calculation and optimization. *Chem. Eng. Technol.* (12), pp. 188-195

Harris, L.S. (1965) Energy and efficiency characteristics of the ejector venturi scrubber. *J. Air Pollution Control Assoc.* 15, (7), pp. 302-305

Hay, K.J.; Liu, Z.C.; Hanratty, T.J. (1998) A backlighted imaging technique for particle size measurements in two-phase flows. *Experiments in fluids*. (25), pp. 226-232

Hesketh, H.E. (1974) Fine particle collection efficiency related to pressure drop, scrubbant and particle properties, and contact mechanism. *J. Air Pollution Control Assoc.* 24, (10), pp. 939-942

Hesketh, H.E.; Engel, A.J.; Calvert, S. (1970) Atomization, a new type for better gas scrubbing. *Atmos. Environ.* (4), pp. 639-645

Higbie, R. (1935) The rate of absorption of a pure gas into a still liquid during short periods of exposure. *Trans. Am. Inst. Chem. Eng.* (31), pp. 365

Hikita, H.; Asai, S.; Nose, H. (1978) Absorption of sulfur dioxide into water. *AIChE J.* 24, (1), pp. 147-149

Hikita, H.; Asai, S.; Takatsuka, T. (1972) Gas absorption with a two - step instantaneous chemical reaction. *Chem. Eng. J.* (4), pp. 31

Hikita, H.; Asai, S.; Tsuji, T. (1977) Absorption of sulfur dioxide into aqueous sodium hydroxide and sodium sulfite solutions. *AIChE J.* 23, (4), pp. 538-544

Hills, J.H. (1995) Behavior of venturi scrubbers as chemical reactors. *Ind. Eng. Chem. Res.* (34), pp. 4254-4259

Hills, J.H.; Azzopardi, B.J.; Barhey, A.S. (1996) Spatial unsteadiness - A way towards intensive gas - liquid reactors. *Trans IChemE.* (74), Part A, pp. 567-574

Himmelblau, D.M.; Bishoff, K.B. (1992) *Análisis y simulación de procesos.* Ed. Reverté. Barcelona

Hollands, K.G.T.; Goel, K.C. (1975) A general method for predicting pressure loss in venturi scrubbers. *Ind. Eng. Chem. Fundam.* 14, (1), pp. 16-22

Hughes, D.T.; Bott, T.R. (1998) Minimum thickness of a liquid film flowing down a vertical tube. *Int. J. Heat and Mass Transf.* 41, (2), pp. 253-260

Ingebo, R.D.; Foster, H.H. (1957) Drop size distribution for cross current breakup of liquid jets in air streams. *NACA Technical Report*. 4807

Johnson, G.R.; Crynes, B.L. (1974) Modelling of a thin-film sulfur trioxide sulfonation reactor. *Ind. Eng. Chem. Proc. Des. Dev.* (13), pp. 6-14

Johnson, I.; LaMer, V.K. (1947) The determination of the particle size of monodispersed systems by the scattering of light. *J. American Chem. Soc.* (69), pp. 1184-1192

Johnstone, H.F.; Feild, R.B.; Tassler, M.C. (1954) Gas absorption and aerosol collection in a venturi atomizer. *Ind. Eng. Chem.* 41, (11), pp. 1601-1608

Johnstone, H.F.; Roberts, M.H. (1949) Deposition of aerosol particles from moving gas streams. *Ind. Eng. Chem.* (41), pp. 2417

King, C.J. (1966) Turbulent liquid phase mass transfer at a free gas - liquid interface. *Ind. Eng. chem. Fund.* 1, (5), pp. 1

Kleinman, L.S.; Reed, X.B. (1995) Interphase mass transfer from bubbles, drops and solid spheres: diffusional transport enhanced by external chemical reaction. *Ind. Eng. Chem. Res.* (34), pp. 3621-3631

Kocamustafaogullari, G.; Smits, S.R.; Razi, J. (1994) Maximum and mean droplet sizes in annular two-phase flow. *Int. J. Heat and Mass Transfer.* 37, (6), pp. 955-965

Koehler, J.L.M.; Feldman, H.A.; Leith, D. (1987) Gas-borne liquid flow rate in a venturi scrubber with two different liquid injection arrangements. *Aerosol Sci. Technol.* 7, pp. 15-29

Krissmann, J.; Siddiqi, M.A.; Lucas, K. (1998) Thermodynamics of SO₂ absorption in aqueous solutions. *Chem. Eng. Technol.* 21, (8), pp. 641-644

Kuznetsov, M.D.; Oratovskii, V.I. (1962) Rate of chemisorption in a venturi - type apparatus. *Int. Chem. Eng.* 2, (2), pp. 185-188

LaMer, V.K.; Barnes, M.D. (1945) Monodispersed hydrophobic colloidal dispersions and light scattering properties. *J. Colloid Sci.* (1), pp. 71-77

Lamourelle, A.P.; Sandall, O.C. (1972) Gas absorption into a turbulent liquid. *Chem. Eng. Sci.* (27), pp. 1035-1043

Langmuir, I.; Blodgett, K. (1946) A mathematical investigation of water droplet trajectories. *A. A. F. Tech. Rep.* 5418.

Lapple, C.E.; Kamack, H.J. (1955) Performance of wet dust scrubbers. *Chem. Eng. Progress.* 51, (3), pp. 110-121

Lasheras, J.C.; Villermaux, E.; Hopfinger, E.J. (1998) Break-up and atomization of a round water jet by a high-speed annular air jet. *J. Fluid Mech.* (357), pp. 351-379

LeClair, B.P.; Hamielec, A.E.; Pruppacher, H.R., Hall, W.D. (1972) A theoretical and experimental study of the internal circulation in water drops falling at terminal velocity in air. *J. Atm. Sci.* (29), pp. 728-740

Lefebvre, A.H. (1989) *Atomization and Sprays*. Hemisphere. New York

Leith, D.; Cooper, D.W.; Rudnick, S.N. (1985a) Venturi scrubbers: pressure loss and regain. *Aerosol Sci. & Technol.* 4, (2), pp. 239-243

Leith, D.; Martin, K.P.; Cooper, D.W. (1985b) Liquid utilisation in a venturi scrubber. *Filtration and Separation.* (22), pp. 191-195

Levich, V.G. (1962) *Physicochemical hydrodynamics*. Prentice-Hall. New Jersey

Lewis, W.K.; Whitman, W.G. Principles of gas absorption. *Ind. Eng. Chem.* 12, (16), pp. 1215

Limiñana de la Fe, G.; Díaz González, F.; Rodríguez Sevilla, J. (1990) Modelización de la absorción de dióxido de azufre en disolución acuosa a bajas concentraciones de reactivos. *Anales de Química.* 87, (2), pp. 231-239

Lin, S.P.; Reitz, R.D. (1998) Drop and spray formation from a liquid jet. *Annu. Rev. Fluid Mech.* (30), pp. 85-105

Maalej, S.; Benadda, B.; Dabaliz, A.; Otterbein, M. (1999) Experimental study on a co-current gas-liquid down flow contactor with gas entrainment by a liquid jet. *Chem. Eng. Technol.* 22, (12), pp. 1043-1049

Mayinger, F.; Neumann, M. (1978) Dust collection in venturi scrubbers. *German Chem. Eng.* 1, pp. 289-293

McCabe, W.L.; Smith, J.C.; Harriott, P. (1991) *Unit operations in chemical engineering*. McGraw-Hill. New York

McCready, M.J.; Hanratty, T.J. (1985) Effect of air shear on gas absorption by a liquid film. *AIChE J.* 31, (12), pp. 2066-2074

Michalski, J.A. (1995) Vertical motion of spherical particles. *Chem. Eng. Technol.* 18, (6), pp. 434-439

Michalski, J.A. (1996) Two-dimensional motion of spherical particles. *Chem. Eng. Technol.* 19, (3), pp. 209-214

Michalski, J.A. (1997) Aerodynamic characteristics of FGD spray towers. *Chem. Eng. Technol.* 20, (2), pp. 108-117

Michalski, J.A. (1998) The influence of spraying angle on aerodynamic characteristics of FGD spray towers. *Chem. Eng. Comm.* (165), pp. 17-40

Mitra, S.K.; Li, X. (1999) A predictive model for droplet size distribution in sprays. *Atomization and Sprays.* 9, (1), pp. 29-50

Montgomery, D.C. (1991) *Diseño y análisis de experimentos*. Grupo Editorial Iberoamericana. México

Muir, D.M.; Kuye, A.O. (1986) Effect of drop size, polydispersity and degree of liquid entrainment on venturi scrubber performance. *4th World Filtration Congress*. Ostend. Belgium, 22-25 April

Neve, R.S. (1988) The performance and modeling of liquid jet gas pumps. *Int. J. Heat and Fluid Flow.* 9, (2), pp. 156-164

Nguyen, D.A.; Rhodes, M.J. (1998) Producing fine drops of water by twin-fluid atomisation. *Powder Technol.* (99), pp. 285-292

Nukiyama, S.; Tanasawa, Y. (1938) Experiments on the atomization of liquids in an air stream. *Trans. Soc. Mech. Engrs. (Japan)*. 5, (18), pp. 63

Okada, B.; Fujimatsu T.; Fujita H.; Honma K. (1994) Some problems on droplet size measurement by immersion liquid method. *Proceedings ICLASS 94*

Okamoto, T.; Takagi, T.; Kaji, T.; Shimazaki, K.; Nakanishi, K. (1998) Studies of the behavior of droplets and the air flow in a hollow-cone spray. *J. Fluids Eng.* (120), pp. 586-592

Oliveira, C.A.; Coury, J.R. (1996) Performance of a venturi scrubber in the removal of inhalable particles from the air. *Brazilian J. Chem. Eng.* 13, (1), pp. 9-20

Overcamp, T.J.; Bowen, S.R. (1983) Effect of throat length and diffuser angle on pressure loss across a venturi scrubber. *J. Air Poll. Control Assoc.* 33, (6), pp. 600-604

Parker, G.J.; Cheong, K.C. (1973). Air-water tests on a venturi for entraining liquid films. *Int. J. Fluid Mech. Sci.* (15), pp. 633-641

Perry , R.H. (1998) *Chemical Engineers' Handbook*. McGraw-Hill. New York

Pitzer, K.S. (1991) *Activity coefficients in electrolyte solutions*. CRC. Boca Raton

Placek, T.D.; Peters, L.K. (1981) Analysis of the particulate removal in venturi scrubbers - Effect of operating variables on performance. *AIChE J.* 28, (1), pp. 31-39

Priestman, G.H.; Tippetts, J.R. (1995) The application of a variable-area jet pump to the external recirculation of hot flue-gases. *J. Institute of Energy*. (68), pp. 213-219

Pulley, R.A. (1997) Modelling the performance of venturi scrubbers. *Chem. Eng. Journal*. (67), pp. 9-18

Rappaport, K.D.; Kettaneh, N.; Wold, S. (1998) Perspectives on implementing statistical modeling and design (SMD) in an industrial/chemical environment. *American Statistician*. 52, (2), pp. 152-159

Ravindram, M. (1987) Response to comments on 'Modeling of a venturi scrubber for the control of gaseous pollutants. *Ind. Eng. Chem. Res.* (26), pp. 1266

Ravindram, M.; Pyla, N. (1985) Modeling of a venturi scrubber for the control of gaseous pollutants. *Ind. Eng Process Des. Develop.* (25), pp. 35-40

Reid, R.C.; Prausnitz, J.M.; Poling, B.E. (1987) *The properties of gases and liquids*. McGraw-Hill. New York

Riazi, M.R. (1986) Estimation of rates and enhancement factors in gas absorption with zero-order chemical reaction and gas-phase mass-transfer resistances. *Chem. Eng. Sci.* 41, (11), pp. 2925-2929

Riazi, M.R. (1996) Modeling of gas absorption into turbulent films with chemical reaction. *Gas Sep. Purif.* 10, (1), pp. 41-46

Riazi, M.R.; Faghri, A. (1986) effect of unterfacial drag on gas absorption with chemical reaction in a vertical tube. *AIChE J.* 32, (4), pp. 696-699

Ripperger, S.; Dau, G. (1980) Berechnung des druckverlustes von venturi-wäschern. *Verfahrenstechnik.* 14, (3), pp. 164-168

Rizk, N.K.; Lefebvre, A.H. (1985) Spray characteristics of spill-return atomizers. *J. Propulsion and Power.* 1, (3), pp. 200-204

Roberts, D.B.; Hill, J.C. (1981) Atomization in a venturi scrubber. *Chem. Eng. Comm.* (12), pp. 33-68

Rudnick, S.N.; Koehler, J.L.M.; Martin, K.P.; Leith, D.; Cooper, D.W. (1986) Particle collection efficiency in a venturi scrubber: Comparison of experiments with theory. *Env. Sci. Technol.* 20, (3), pp. 237-242

Sanger, N.L. (1970) An experimental investigation of several low-area ratio water jet pumps having throat lengths of 7.25 diameters. *ASME Journal of Basic Engineering.* 92, (1), pp. 11-20

Schiller L.; Nauman, A. (1933) Über die Grundlegenden berechnungen bei der schwerkraftaufbereitung. *Ver. Deutsch. Ing.* 48, (15), pp. 318-320

Schlichting, H. (1968) *Boundarylayer Theory.* McGraw-Hill. New York

Schmidt, B.; Stichlmair, J. (1991) Two-phase flow and mass transfer in scrubbers. *Chem. Eng. Technol.* 14, (1), pp. 162-166

Schultes, M. (1998) Absorption of sulfur dioxide with sodium hydroxide solution in packed columns. *Chem. Eng. Technol.* 21, (2), pp. 201-209

Semrau, K.T.; Marynowski, C.W.; Lunde, K.E.; Lapple, C.E. (1958) Influence of power input on efficiency of dust scrubbers. *Ind. Eng. Chem.* 50, (11), pp. 1615-1620

Sherwood, T.K.; Pigford, R.L.; Wilke, C.R. (1975) *Mass transfer*. McGraw-Hill. New York

Shimizu, Y.; Nakamura, S.; Kuzuhara, S.; Kurata, S. (1987) Studies of the configuration and performance of annular type jet pumps. *J. Fluids Eng.* (109), pp. 205-212

Sinclair, D.; LaMer, V.K. (1949) Light scattering as a measure of particle size in aerosols. *Chem. Revs.* (44), pp. 245-267

Sirignano, W.A. (1993) Fluid dynamics of sprays. *J. Fluids Eng.* (115), pp. 354-378

Snyder, H.E.; Reitz, R.D. (1998) Direct droplet production from a liquid film: a new gas-assisted atomization mechanism. *J. Fluid Mech.* (375), pp. 363-381

Soldati, A.; Andreussi, P. (1996) The influence of coalescence on droplet transfer in vertical annular flow. *Chem. Eng. Sci.* 51, (3), pp. 353-363

Sparks, L.E.; Ramsey, G.H.; Daniel, B.E. (1981) Particle collection by a pilot plant venturi scrubber downstream from a pilot plant electrostatic precipitator. *Atm. Env.* (15), pp. 65-72

Steinberger, R.L.; Treybal, R.E. (1960) Mass transfer from a solid soluble sphere to a flowing liquid stream. *AIChE J.* (6), pp. 227

Taheri, M.; Haines, G.F. (1969) Optimization of factors affecting scrubber performance. *J. Air Pollution Control Assoc.* (19), pp. 427-433

Taheri, M.; Sheih, Ch. (1975) Mathematical modelling of atomizing scrubber, *AIChE J.* 21, (1), pp. 153-157

Takahashi, F.; Schmoll, W.J.; Dressler, J.L. (1995) Characteristics of a velocity-modulated pressure-swirl atomizing spray. *J. Propulsion and Power.* 11, (5), pp. 955-963

Talaie, M.R.; Fathikalajahi, J.; Taheri, M. (1997) Mathematical modeling of SO₂ absorption in a venturi scrubber. *J. Air. & Waste Manag. Assoc.* (47), pp. 1211-1215

Talens - Aleson, F.I. (1998) The modelling of falling film chemical reactors. *Chem. Eng. Sci.* 54, (12), pp. 1871-1881

Teixeira, J.C.F. (1988) *Turbulence in annular two-phase flow*. PhD dissertation. University of Birmingham

Uchida, S.; Wen, C.Y. (1973) Gas absorption by alkaline solutions in a venturi scrubber. *Ind. Eng. Chem. Process. Des. Develop.* 12, (4), pp. 437-443

Van Dam, M.H.H.; Corriou, J.P.; Midoux, N.; Lamine, A.S.; Roizard, C. (1999) Modeling and measurement of sulfur dioxide absorption rate in a laminar film reactor. *Chem. Eng. Sci.* 54, (21), pp. 5311-5318

Velan, M.; Ramanujan, T.K. (1992) Gas-liquid mass transfer in a down flow jet loop reactor. *Chem. Eng. Sci.* 47, (9/11), pp. 2871-2876

Virkar, P.D.; Sharma, M.M. (1975) Mass transfer in venturi scrubbers. *Can. J. Chem. Eng.* (53), pp. 512-516

Viswanathan, S. (1997) Modelling of venturi scrubber performance. *Ind. Eng. Chem. Res.* (36), pp. 4308-4317

Viswanathan, S. (1998a) Examination of liquid film characteristics in the prediction of pressure drop in a venturi scrubber. *Chem. Eng. Sci.* 53, (17), pp. 3161-3175

Viswanathan, S. (1998b) Development of a pressure drop model for a variable throat venturi scrubber. *Chem. Eng. J.* (71), pp. 153-160

Viswanathan, S.; Gnyp, A.W.; St Pierre, C.C. (1984) Examination of gas-liquid flow in a venturi scrubber. *Ind. Eng. Chem. Fundam.* (23), pp. 303-308

Viswanathan, S.; Gnyp, A.W.; St Pierre, C.C. (1985) Annular flow pressure drop for Pease-Anthony-type venturi scrubbers. *AIChE J.* 31, (12), pp. 1947-1958

Viswanathan, S.; Gnyp, A.W.; St Pierre, C.C. (1985) Estimating film flow rate in a venturi scrubber. *Particulate Sci. & Technol.* (15), pp. 65-76

Viswanathan, S.; St.Pierre, C.C.; Gnyp, A.W. (1983) Jet penetration measurements in a venturi scrubber. *Canadian J. Chem. Eng.* (61), pp. 504-508

Volgin, B.P.; Efimova, T.F.; Gofman, M.S. (1968) Absorption of sulfur dioxide by ammonium sulfite-bisulfite solution in a venturi scrubber. *Int. Chem. Eng.* 8, (1), pp. 113-118

Wang, D.; Wypych, P.W. (1995) Water-only performance of proportioning jet pumps for hydraulic transportation of solids. *Powder Technol.* (84), pp. 57-64

Wang, J.; Shejiao, H.; Wei, F.; Yu, Z.; Jin, Y. (1997) An axial dispersion model for gas-liquid reactors based on the penetration theory. *Chem. Eng and Processing.* (36), pp. 291-299

Wang, X.F.; Lefebvre, A.H. (1987) Mean drop sizes from pressure-swirl nozzles. *J. Propulsion and Power.* 3, (1), pp. 11-18

Wessman, E.D. (1981) *Experiments on droplet size distributions in a laboratory scale venturi scrubber.* PhD Thesis. University of Waterloo

Whalley, P.B.; Hutchinson, P.; Hewitt, G.F. (1973) The calculation of critical heat flux in forced convective boiling. *European two-phase flow group meeting.* Brussels. (4-7 June 1973), paper B-4.

Witte, J.H. (1965) Efficiency and design of liquid-gas ejectors. *British Chem. Eng.* 10, (9), pp. 602-607

Witte, J.H. (1969) Mixing shocks in two-phase flow. *J. Fluid Mech.* 36, (part A), pp. 639-655

Wright, P.C.; Meeyoo, V.; Soh, W.K. (1997) A study of ozone mass transfer in a cocurrent downflow jet pump contactor. 20, (1), pp. 17-32

Xianlou, M; Dazhang, H.; Rongji, H.; Taiping, X. (1992) Gas holdup and volumetric liquid phase mass transfer coefficients in a downjet loop reactor. *Chem. Eng. J.* (49), pp. 49-54

Yamauchi, J.; Wada, T.; Kamei, H. (1963) The pressure drop across venturi scrubbers. *Kagaku Kogaku*. 27, (12), pp. 974-997

Yang, R.; Jou, T.M. (1998) Non-absorbable gas effect on the wavy film absorption process. *Inj. J. Heat and Mass Transf.* (41), pp. -3668

Yoshimura, P.N.; Nosoko, T.; Nagata, T. (1996) Enhancement of mass transfer into a falling laminar liquid film by two-dimensional surface waves - Some experimental observations and modeling. *Chem. Eng. Sci.* 51, (8), pp. 1231-1240

Yule, A.J.; Widger, I.R. (1996) Swirl atomizers operating at high water pressure. *Int. J. Mech. Sci.* 38, (8-9), pp. 981-999

Yung, S.C.; Barbarika, H.F.; Calvert, S. (1977) Pressure loss in venturi scrubbers. *J. Air Pollution Control Assoc.* 27, (4), pp. 348-350

Zaidi, S.H.; Altunbas, A.; Azzopardi, B.J. (1998) A comparative study of phase doppler and laser diffraction techniques to investigate drop sizes in annular two-phase flow. *Chem. Eng. Journal.* (71), pp. 135-143.